

Speed bump „40”

Purpose:

- estate roads, car parks
- tracts of various widths

Material:

- Vulcanised rubber
- Reflective element - "cat's eyes"
- Metal reinforcements for mounting



Dimensions:

Item name		Length (mm)	Width (mm)	Height (mm)	Weight (kg)
Version 1	(centre piece)	400	500	50	8,5
	(end piece)	400	200	50	1,7
Version 2	(centre piece)	400	500	75	10,5
	(end piece)	400	200	75	2,1

Colour:


- Black, yellow
- Reflective element "cat's eyes"

Technical parameters:


Parameters	Value	Unit	Standard / Method
Tensile strength	≥ 4,0	MPa	PN-ISO 37
Hardness	≥ 60	°ShA	PN-EN ISO 868:2005
Water absorption	≤ 2	%	PN-EN ISO 62
Tolerance - length, width	± 2	%	of nominal
Tolerance - height	± 2	%	of nominal
Tolerance- weight	± 2	%	of nominal

Technical drawings:

Version 1. height 50 cm



Version 2. height 75 cm



Packing:

The method of packaging is determined individually, depending on the order.

Description with product name, quantity, batch number and packing date on the pallet.

Identification:

Product- on the underside of the product information about the date of production.

Pallet- product name, quantity, pallet identification number, packing date, quality control stamp.

Storage:

The products should be stored on pallets in protective film and protected from external weather conditions.

The products may be stored for a longer period of time only in closed, ventilated rooms without humidity, after removing the protective film. Storage temperature: max 40 °C

Health, safety and fire conditions:

Conditions for storage and use of the product- must meet all requirements for storage and use of rubber materials.